

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika-Trocal Liquid PVC (Seam Sealant)

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Special system.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Harmful	R22: Harmful if swallowed.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015




Version 1.1

Print Date 21.01.2015

Carcinogenic Category 3 R40: Limited evidence of a carcinogenic effect.
Irritant R36/37: Irritating to eyes and respiratory system.
R19: May form explosive peroxides.
R67: Vapours may cause drowsiness and dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P281 Use personal protective equipment as required.

Response:
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 203-726-8 tetrahydrofuran

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
tetrahydrofuran 109-99-9 203-726-8 01-2119444314-46-XXXX Contains: methanol >= 0,1 - <= 0,5 %	F; R11-R19 Xi; R36/37 Carc.Cat.3; R40 Xn; R22 R67	Flam. Liq.2; H225 Acute Tox.4; H302 Eye Irrit.2; H319 Carc.2; H351 STOT SE3; H336 STOT SE3; H335	>= 50 - <= 100
cyclohexanone 108-94-1 203-631-1	R10 Xn; R20	Flam. Liq.3; H226 Acute Tox.4; H332	>= 10 - < 20

Remarks : Substances with a workplace exposure limit

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder
Excessive lachrymation
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

Risks : irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
tetrahydrofuran	109-99-9	TWA	50 ppm 150 mg/m3	2000/39/EC

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

		STEL	100 ppm 300 mg/m ³	2000/39/EC
		TWA	50 ppm 150 mg/m ³	GB EH40
		STEL	100 ppm 300 mg/m ³	GB EH40
cyclohexanone	108-94-1	TWA	10 ppm 40,8 mg/m ³	2000/39/EC
		STEL	20 ppm 81,6 mg/m ³	2000/39/EC
		TWA	10 ppm	GB EH40
		STEL	20 ppm	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
cyclohexanone	108-94-1	cyclohexanol: 2mmol/mol creati- nine (Urine)	Post shift	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields
 Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
 Butyl rubber/nitrile rubber gloves (0,4 mm),
 Contaminated gloves should be removed.
 Suitable for permanent exposure:
 Viton gloves (0.4 mm),
 breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
 organic vapor filter (Type A)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: various
Odour	: ether-like
Odour Threshold	: No data available
Flash point	: -1 °C
Ignition temperature	: No data available
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 12 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: Note: not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: ca. 65 °C
Vapour pressure	: ca.200 hPa
Density	: ca.0,946 g/cm ³ at 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20,5 mm ² /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

tetrahydrofuran :

Acute oral toxicity : LD50 Oral rat: 1.650 mg/kg

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

Acute inhalation toxicity	: LC50 rat: 54 mg/l Exposure time: 4 h
Acute dermal toxicity	: LD50 Dermal rat: > 2.000 mg/kg
cyclohexanone : Acute oral toxicity	: LD50 Oral rat: 1.530 mg/kg
Acute inhalation toxicity	: LC50 rat: 10,7 mg/l Exposure time: 4 h
Acute dermal toxicity	: LD50 Dermal rabbit: 948 mg/kg

Skin corrosion/irritation

Product

No data available

Serious eye damage/eye irritation

Product

Causes serious eye irritation.

Respiratory or skin sensitisation

Product

No data available

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : Suspected of causing cancer.

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocacal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

cyclohexanone :

Toxicity to fish : LC50: 527 mg/l, 96 h, Fish

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1133
14.2 Description of the goods : ADHESIVES
14.3 Class : 3
14.4 Packing group : II
Classification Code : F1
Labels : 3
Tunnel restriction code : (D/E)
14.5 Environmentally hazardous : no

IATA

14.1 UN number : 1133
14.2 Description of the goods : Adhesives
14.3 Class : 3
14.4 Packing group : II
Labels : 3
14.5 Environmentally hazardous : no

IMDG

14.1 UN number : 1133
14.2 Description of the goods : ADHESIVES
14.3 Class : 3
14.4 Packing group : II
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-D
14.5 Marine pollutant : no

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Highly flammable



Harmful

R-phrases) : R11 Highly flammable.
R19 May form explosive peroxides.
R22 Harmful if swallowed.
R36/37 Irritating to eyes and respiratory system.
R40 Limited evidence of a carcinogenic effect.
R67 Vapours may cause drowsiness and dizziness.

S-phrases) : S36/37 Wear suitable protective clothing and gloves.

Hazardous components which must be listed on the label:

- 203-726-8 tetrahydrofuran

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

VOC-CH (VOCV) : 80 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

VOC-EU (solvent) : 80 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R10	Flammable.
R11	Highly flammable.
R19	May form explosive peroxides.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R36/37	Irritating to eyes and respiratory system.
R40	Limited evidence of a carcinogenic effect.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity - single exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika-Trocal Liquid PVC (Seam Sealant)



Revision Date 21.01.2015

Version 1.1

Print Date 21.01.2015

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.



Changes as compared to previous version !