

# PRODUCT DATA SHEET

## S-Felt A-300

### POLYPROPYLENE LEVELLING LAYER

#### PRODUCT DESCRIPTION

S-Felt A-300 is a levelling layer made of polypropylene (PP).

#### USES

- Levelling, separation and protection layer between Sika® membranes and rough surfaces.

#### CHARACTERISTICS / ADVANTAGES

- Bitumen resistant
- Easily applied



#### PRODUCT INFORMATION

<b>Chemical Base</b>	100% polypropylene (PP)	
<b>Packaging</b>	Rolls wrapped individually in a black PE-foil.	
	Length	50,00 m
	Width	2,00 m
	Weight	30,00 kg
<b>Appearance / Colour</b>	Surface	Structured
	Colour	Multi-coloured
<b>Shelf Life</b>	5 years from date of production.	
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Always refer to packaging.	
<b>Length</b>	50,00 m	
<b>Width</b>	2,00 m (+/- 2 %)	

<b>Thickness</b>	1,9 mm (+/- 10 %)	(EN 9863)
<b>Mass per unit area</b>	300 g/m <sup>2</sup> (+/- 10 %)	(EN 9864)

## TECHNICAL INFORMATION

<b>Tensile Strength</b>	longitudinal	≥ 300 N/50 mm	(EN 10319)
	transversal	≥ 400 N/50 mm	
<b>Elongation</b>	longitudinal	≤ 75 %	(EN 10319)
	transversal	≤ 75 %	
<b>Reaction to Fire</b>	Class E	(EN 13501-1)	

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	-20 °C min. / +60 °C max.
<b>Substrate Temperature</b>	-30 °C min. / +60 °C max.

## APPLICATION INSTRUCTIONS

### APPLICATION

S-Felt A-300 is loose laid accordance with Sarnafil® installation instructions.  
 Adjoining sheets must overlap at least 50 mm.

## LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- Do not use for permanent exposure to UV radiation.

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland



Product Data Sheet  
S-Felt A-300  
July 2019, Version 01.01  
020945051050000003

S-FeltA-300-en-GB-(07-2019)-1-1.pdf