

# Sika-Trocal® Cleaner L 100

## Product Description

Mixture of high volatile solvents

## Uses

Cleaner to remove local contamination from Sika-Trocal® roof waterproofing and waterproofing membrane seams and preparation of old Sikaplan® PVC membranes for certain applications. Sika-Trocal® Cleaner L 100 is suitable for diluting Sika-Trocal® C 733 adhesive and degreasing metal sheets. Also applicable for preparation of PVC membranes for solvent welding and Sikalastic® Primer PVC.

## Characteristics / Advantages

- Dissolves contamination of adhesive resin, mastic and bitumen
- Evaporates quickly
- Highly flammable
- The cleaner may be suitable to clean metal tools

## Tests

### Approvals / Standards

- Quality management system EN ISO 9001/14001

## Product Data

### Form

Consistency liquid

Colour transparent

Packaging Can: 4 kg

## Storage

### Storage Conditions

Store cool and dry in originally sealed container protected from direct sunshine. The product is highly flammable: Safety regulations regarding storage and handling of dangerous goods must be observed.

### Shelf-Life

24 months from date of production if stored properly in original, unopened and undamaged sealed container. Expiry date on can.

Roofing



---

**Technical Data**

---

**Chemical Basis** Mixture of high volatile solvents

---

**Density** 0.9 kg/l

---

**System Information**

---

**Processing Requirements / Limits**

---

**Ambient Temperature** At least -30°C

---

**Substrate Temperature** At least -20°C

---

**Limits** Dissolves thermoplastics not resistant to solvents (e.g. polystyrene, polycarbonate, acrylics)  
Do not use the cleaner to wash large areas of roof surface.

---

**Processing**

---

**Application Guideline** Based on the valid installation instructions of the relevant roof waterproofing membrane.

**Application Method** Application as cleaner:  
Sika-Trocal® Cleaner L 100 has high dissolution effect on textile colours and dirt. In order to prevent discolorations on the membrane surface, it is recommended to use white textiles as cleaning cloths. Spilled Sika-Trocal® Cleaner L 100 must be soaked up with dry cloths immediately. Cleaner on the membrane surface must be thoroughly evaporated prior to welding of seams or use of Sikalastic® Primer PVC.

Application as adhesive dilutant:  
See the Product Data Sheet of Sika-Trocal® C 733 for more information.

**Notes of Application / Limits** Sika-Trocal® Cleaner L 100 can reduce the seam quality and should only be used on heavily soiled areas.

Use solvent resistant gloves and eye protection glasses during application.  
The least amount of cleaner attacks thermoplastic surfaces.  
Sika-Trocal® Cleaner L 100 contains high volatile and flammable solvents.  
Application in closed rooms is allowed only with sufficient room ventilation.

Residues of material will evaporate rapidly.

**Important Remarks**

---

**Tool Cleaning** Tools and equipment must be cleaned immediately after use.

---

**Value Base** All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

**Local Restrictions** Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

**Health and Safety Information** For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data. REACH relevant information is available in the most recent SDS.

**Legal note** The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



**Sika Limited**, Watchmead, Welwyn Garden City,  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444, Fax: 01707 329129, Email: [sika-trocal@uk.sika.com](mailto:sika-trocal@uk.sika.com)  
[www.sikatrocal.co.uk](http://www.sikatrocal.co.uk)  
Registered in England: Number 226822

Sika-Trocal® Cleaner L 100

**Sika-Trocal®**