

Sika® Dukmat® Walkway PVC

Walkway for Sika® PVC roofing membranes

Product Description PVC Open grid "duckboard" design with cross directional top ribs.

Uses Sika® Dukmat® Walkway PVC is used with Sika PVC roofing membranes.

Characteristics / Advantages

- Ease of application
- Recyclable

Tests

Approval / Standards

- Quality Management system in accordance with EN ISO 9001/14001.
- BS7976 low risk

Product Data

Form

Appearance Textured surface

Storage

Storage conditions Sika® Dukmat® Walkway PVC should be stored away from harsh influences.

Shelf-life Sika® Dukmat® Walkway PVC does not expire if stored correctly.

Technical Data

Material basis Flexible plasticised polyvinyl chloride.

Width 600mm

Length 10000mm

Thickness 14mm

Mass per unit area 0.74kg/m

Roofing



Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire
AL7 1BQ
United Kingdom
Phone +44 1707 394444
Telefax +44 1707 329129
www.sika.co.uk



Application**Conditions / Limits****Temperature**

The use of Dukmat is limited to applications with a winduplift of up to 2.4kN/m² and geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

Notes on installation limits**Installation**

Installation works to be carried out only by Sika Contractors.

Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire
AL7 1BQ
United Kingdom
Phone +44 1707 394444
Telefax +44 1707 329129
www.sika.co.uk

Ecology, Health and Safety Information	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
Protective Measures	Local safety regulations must be observed.
Transportation Class	The product is not classified as hazardous good for transport.
Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Disclaimer	The information, and, in particular, the recommendations relating to the application and end- use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited
 Watchmead
 Welwyn Garden City
 Hertfordshire
 AL7 1BQ
 United Kingdom
 Phone +44 1707 394444
 Telefax +44 1707 329129
www.sika.co.uk

