

Sika® Flexistrip

Preformed Strip Sealant for use with the Sika-Trocal® Liquid Detailing System.

Product Description Sika® Flexistrip is a preformed strip sealant reel on a paper release liner for use with Sikalastic®-621 TC in the Sika-Trocal® Liquid Detailing System.

Applications For treatment of boltheads and fixings prior to application of Sikalastic®-621 TC.

Technical Data

Colour Off -White

Length 15 metre

Width 50mm

Storage

Storage Conditions Store in original packaging in a location away from sources of heat or ignition, dampness and extremes of temperature. Keep protected from rain and sunlight.

Substrate Preparation The substrate must be firm, sound, clean and dry.

Installation Method / Tools

Where necessary, materials should be cut with a knife or scissors. After cleaning and priming the fixing as required, pre-cut 50mm squares, remove the backing and fix by light pressure to the edges of the patches. Do not exert hard pressure in an attempt to form the tape to contours. On completion, keep clean and avoid foot pressure damage prior to coating with the Sikalastic®-621 TC.

Notes on Installation / Limits

Installation works to be carried out only by Licensed Sika-Trocal® Contractors.

Temperature limits for the installation of the membrane:

Substrate temperature: At least +5 °C
Ambient temperature: At least +5 °C

Roofing



Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Legal Note

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and guarantee are valid.



Sika Limited, Watchmead, Welwyn Garden City,
Hertfordshire, AL7 1BQ
Tel: 01707 394444, Fax: 01707 329129, Email: sika-
trocal@uk.sika.com
www.sikatrocal.co.uk
Registered in England: Number 226822

Sika-Trocal®