

Product Data Sheet

Edition 08.2015

Identification no. 02 09 02 9 030 00000004

Version no. 01

Sika® Reemat Premium

Glass fibre mat reinforcement for Sikalastic®-621 TC used in the Sika-Trocal® Liquid Detailing System

Product Description

Sika® Reemat Premium is glass fibre reinforcement mat.

Uses

Sika® Reemat Premium is used as reinforcement with the Sika-Trocal® Liquid Detailing System.

Characteristics / Advantages

Easy and quick application of details
Adapts to most shapes and profiles on the substrate surface

Product Data

Form

Appearance / Colours

White

Packaging

Rolls
1.3 m wide by 90m (approx)

Storage

Storage Conditions / Shelf Life

Stored properly in original, unopened and undamaged sealed packaging in dry conditions, flat and wrinkle-free. Temperature 10 – 35 °C. Keep dry.

Roofing



Technical Data

Chemical Basis Random glass fibre matting

Mass Per Unit Area 225 g/m²

System Information

System Structure

Detailing

For use with problematic detailing with Sika-Trocal® S/SG/SGK membranes to for a complete waterproofing system.



Build up: Sikalastic® -621 TC applied in 2 coats, reinforced with Sika® Reemat Premium

Substrates: Specific substrates and Sika-Trocal® membranes

Primer: Please refer to Sikalastic® Primer chart below

Dry film thickness: 1.8 mm

(TC and TC)

Consumption: first layer TC: ≥ 1.4 kg/m² (1L/m²)

Consumption: second layer TC: ≥ 1.4 kg/m² (1L/M²)

Application Instructions

Application Method

Detailing

Apply first layer of Sikalastic®-621 TC and roll in the Sika® Reemat Premium whilst wet. Ensure there are no bubbles or creases and that any laps overlap by a minimum of 50mm. Prior to the application of a second layer of Sikalastic®-621 TC the indicated waiting time in Sikalastic®-621 TC PDS should be achieved.

Notes on Application / Limitations

Sika® Reemat Premium is designed to use in combination with Sikalastic®-621 TC.

Roofing

Value Base All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Legal Note The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited, Watchmead, Welwyn Garden City,
Hertfordshire, AL7 1BQ
Tel: 01707 394444, Fax: 01707 329129, Email: sika-trocal@uk.sika.com
www.sikatrocal.co.uk
Registered in England: Number 226822



Sika-Trocal®