

# S-Felt A 300

## Levelling-layer

---

### Product Description

S-Felt A 300 is a levelling-layer made of polypropylene (PP)

---

### Uses

S-Felt A 300 is used as a levelling-layer between Sika-Trocal<sup>®</sup> membranes and rough surfaces.

---

### Characteristics / Advantages

- Not Bitumen resistant
- Non decaying
- High resistance to bacterial infestation
- Long lifespan
- Ease of application
- Recyclable

---

### Tests

---

#### Approvals / Standards

- Reaction to fire according to EN 13501-1
- Quality management system EN ISO 9001/14001

---

### Product Data

---

#### Form

---

#### Appearance

Surface: structured

---

#### Colour

Coloured

---

#### Packaging:

S-Felt A 300 rolls are wrapped individually in black PE-foil.

Roll length: 50.00 m  
Roll width: 2.00 m  
Roll weight: 30.00 kg

---

### Storage

---

#### Storage Conditions

S-Felt A 300 rolls should be stored at dry conditions and in horizontal position, protected from direct sunlight.

---

#### Shelf-Life

S-Felt A 300 does not expire during correct storage.

---



---

## Technical Data

---

<b>Material Basis</b>	100 % polypropylene (PP)	
<b>Length</b>	50.00 m	
<b>Width</b>	2.00 m (+/- 2 %)	
<b>Thickness</b>	1.9 mm (+/- 10 %)	EN 9863
<b>Mass per unit area</b>	300 g/m <sup>2</sup> (+/- 10%)	EN 9864
<b>Reaction to fire</b>	Class E	EN 13501-1
<b>Tensile strength:</b> longitudinal transversal	≥ 300 N/50 mm ≥ 400 N/50 mm	EN 10319
<b>Elongation:</b> longitudinal transversal	≤ 75 % ≤ 75 %	EN 10319

---

---

## System Information

---

### System Structure

Compatible products: All types of Sika-Trocal® membranes

---

### Application Conditions / Limits

---

#### Resistance

Not applicable for permanent exposure to UV irradiation.

---

### Installation Instructions

---

#### Application Method

S-Felt A 300 is loose laid according to the valid installation instructions for Sika-Trocal®.

Adjoining sheets must overlap at least 50 mm.

---

#### Notes on Installation / Limits

Installation works must be carried out only by Sika instructed contractors for roofing.

Temperature limits for the installation of the S-Felt A 300:

Substrate temperature: -30°C min. / +60°C max.

Ambient temperature: -20°C min. / +60°C max.

Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5°C. Please observe information given by Product Data Sheets.

Special measures may be compulsory for installation below +5°C ambient temperature due to safety requirements in accordance with national regulations.

---

<b>Value Base</b>	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
<b>Local Restrictions</b>	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
<b>Ecology, Health and Safety Information</b>	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
<b>Protective Measures</b>	Fresh air ventilation must be ensured, when working (welding) in closed rooms. Local safety regulations must be observed.
<b>Transportation Class</b>	The product is not classified as hazardous good for transport.
<b>Disposal</b>	The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

**Legal note:** The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited  
 Watchmead  
 Welwyn Garden City  
 Hertfordshire  
 AL7 1BQ  
 United Kingdom  
 Phone +44 1707 394444  
 Telefax +44 1707 329129  
[www.sika.co.uk](http://www.sika.co.uk)  
 email: [sales@uk.sika.com](mailto:sales@uk.sika.com)



Certificate No. EMS 4308



Certificate No. FM 12504