

Sika® Flexible Rubber Couplings

Flexible couplings for low pressure connecting of S-Drain, Outlets to pipework

Product Description

Sika® Flexible Rubber Couplings are manufactured from high performance EPDM with corrosion resistant grade 300 stainless steel end clamps.

- Synthetic rubber product.
- Surface coated in lubricant / release agent.
- Stainless steel bands.

Uses

The low pressure connection of Sarnafil S-Drain, Outlets to pipework.

Characteristics / Advantages

- Quick and easy to install.
- Provides a reliable and flexible connection.
- Can be used on any pipe material.

Product Data

Standards/Approvals

- The product is manufactured to the BS EN 295 Standard which has a requirement for the rubber to be compliant with BS EN 681 Part 1.

Appearance / Colours

Body:	Black
Bands:	Metallic - Stainless Steel

Size

As per current price list.

Packaging

Sika® Flexible Rubber Couplings are boxed individually or collectively in cardboard.

Storage Conditions / Shelf-Life

Protected from direct sunlight, strong artificial light, radiation and ozone. Product does not expire in storage if correctly stored.



Application Details

Connection Quality

The connection surface must be uniform, smooth and free of any sharp protrusions or burrs, etc.

Application

Conditions / Limits

Temperature

The use of Sika® Flexible Rubber Couplings are suitable for normal water drainage at a continuous temperature of no more than 80°C.

Compatibility

Not resistant to tar, bitumen, oil and solvent containing materials.

Installation Instructions

Installation Method / Tools

Installation procedure:

Push onto connections and tighten steel end clamps with a screwdriver.

Protective Measures

Gloves can be worn when handling. Avoid contact with eyes.

- Skin contact: Wash with soap and water.
 - Eye contact: Irrigate with water.
 - Seek medical advice if symptoms persist.
-





Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
Ecology, Health and Safety Information	The product does not fall within the EU-regulation of hazardous goods. As a result, a material safety data sheet following EU-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
Protective Measures	Regulatory Safety requirements must be observed.
Disposal	The material is recyclable. Any disposal must be in accordance with regulatory guidelines.
Transportation Class	The product is not classified as hazardous good for transport.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and guarantee are valid.

Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ
Registered in England: 226822

